5151 Plug-In Heat Detector





Models Available

5151 Plug-In Heat Detector

Description

5151 Plug-in HEAT Detectors offer superb performance and Reliability in a sleek, low-profile design.

The 5151 thermal detector meets the needs for Applications where rapid response is vital and rapid temperature increases would only be caused by a fire Emergency. The detector initiates an alarm in response to both rapid Rate-of-rise conditions (increases in excess of 15 F per minute) and fixed heat (135 F). This enables the heat Detector to communicate an alarm to the central control panel prior to reaching its fixed set point for high rates of Rise, providing a timely response to both rapid and slow temperature increases.

A full line of accessories are available for this product.

Features

- Low standby current
- Compatible with 400 Series product
- Two visible LEDs "blink" in standby and provide a 360 field viewing angle
- Detector head plugs easily into base
- Built-in test switch
- Wide variety of mounting bases with built-in shorting spring

Agency Listing





Specifications

50 mm installed in B401 Base Height:

102 mm installed in B401 Base Diameter:

2.8 oz. (80 g) Weight:

 $0 \,\mathrm{C}$ to $38 \,\mathrm{C}$ (32 F to $100 \,\mathrm{F}$) Operating Temperature Range:


10% to 93% Relative Humidity, non-condensing Operating Humidity Range:


8.5 to 35VDC Operating Voltage: 80 μA @ 24VDC **Standby Current:**

10mA Min. 130mA Max. (Must be limited by control panel) Alarm Current:

Reset by momentary power interruption. Latching Alarm: 57 °C (135 °F) Fixed or 15 °F /min rate-of-rise Sensitivity:

Appearence





Ordering Information

Ordering Model	Description	UL	FM	UOM
5151	Plug-In Heat Detector	Yes	Yes	EA
B401	Plug-In Detector Base, 4"	Yes	Yes	EA
B401B	Plug-In Detector Base, 6.2"	Yes	NA	EA
B401-WP	Water proof Plug-In Detector Base, 4"	NA	NA	EA



System Sensor Headquarters 3825 Ohio Avenue St. Charles, IL 60174 Ph: 630-377-6580 Fx: 630-377-6495 Free Phone: 800-736-7672 Web: www.systemsensor.com Web: www.systemsensor.com.cn Fx: 44 (0) 1527 406699 Fx: 54 11 4324-5999

System Sensor China 28 Tuan Jie South Road, Hi-Tech Development Zone Xi'an, 710075, China Ph: +86 29 85387800 Fx: +86 29 88895930

Ph: 905-812-0767 Fx: 905-812-0771

System Sensor Canada System Sensor Italy Ph: 39 040 949 0111 Fx: 39 040 382 137

System Sensor Europe System Sensor Mexico Ph: 44 (0) 1527 406700 Ph: 54 11 4324-1909

System Sensor Far East Ltd System Sensor India Ph: 852 21919003 Ph: 91 124 2371770-270 Fx: 852 27366580 Fx: 91 124 2373118

System Sensor Singapore Ph: 65 6273 2230

System Sensor Australia Ph: 61-3-5428 1142 Fx: 61-3-5428 1172